

DATASHEET

Wall Liner

Wall liner



- for compound seals with Okumul DF, Servoflex DMS 1KPlus SuperTec, Servoflex DMS 1K schnell SuperTec and Kiesel sealing membrane
- for sealing pipe openings
- very elastic, with high resilience
- Expansion sleeves: 20 - 40 mm / 50 - 70 mm / 93 - 146 mm

PRODUCT DESCRIPTION

The **wall liner** is a highly elastic expansion sleeve which is fleece-laminated on both sides. Ideal for sealing pipe openings in conjunction with the chemical-resistant seal **Okumul PU-FCA**, the liquid sealing film **Okumul DF**, the flexible waterproofing slurries **Servofix DMS 1K Plus SuperTec** and **Servoflex DMS 1K-rapid SuperTec** as well as in combination with the sheet-type seal **Kiesel sealing sheet** and the sealing glue **Oka DK** and/or specialised adhesive **Okumul Ki Fix**.

PROCESSING

Embed the **wall liner** in the first application while still fresh, then rework completely with the second/third application. Observe the minimum coating thickness for the seal. Observe the technical data sheet for the sealing compound used.

PACKAGING

Product description	Item no.	Item no.
25 pc./box expansion sleeve 20-40 mm	60012	4015705600123
25 pc./box expansion sleeve 50-75 mm	60362	4015705603629
10 pc./box expansion sleeve 93-146 mm	60363	4015705603636

The aforementioned information, especially the proposals for processing and utilizing our product, is based on our knowledge and experience. We recommend that you carry out your own tests in every case to ensure the suitability of our products for the intended process and processing purposes because of the different materials and the working conditions which lie beyond our area of influence. No liability can be derived from this advice or from verbal advice, unless we are responsible for (criminal) intent or gross negligence in this respect.

Revised: 03.02.2022/rk