

DATASHEET

Self adhering waterproofing corner tape

Self adhering
waterproofing corner tape



- self adhering interior/exterior use
- will adhere to various substrates
- lap joint self-sealing
- easy to install
- wet and humid areas

PRODUCT DESCRIPTION

The ideal **self-adhesive sealing tape** for corners, expansion and connection joints in conjunction with Kiesel waterproofing systems, liquid applied **Okamul DF** and the flexible cement based **Servoflex DMS 1K Plus SuperTec** and **Servoflex DMS 1K-schnell SuperTec** and the two-component polyurethane resin-based **Okamul PU-FCA**. Suitable for mineral substrates and substrates including stainless steel, aluminum and plastic.

PROCESSING

The surface must be dry and free of dirt, dust and be free of release agents. Vacuum mineral based substrates first to remove dust completely and prime with **Okatmos® UG 30** or **Okamul GG**. Metal substrates must be degreased with acetone.

Install sealing tape with designated Kiesel waterproofing membranes. Sealing tape joints must overlap at least 6 cm. Here, note the final thickness. The technical data sheets must be observed.

SPECIFICATIONS

Color	white/grey
Roll width	100 mm
Thickness	ca. 0,85 mm
Application temperature	-31 °F to 158 °F (- 35 °C to + 70 °C)

PACKAGING

Product description	Item no.	Item no.
10 m roll in a cardboard box	60075	4015705600758

The aforementioned information, especially the proposals for processing and utilizing our product, is based on our knowledge and experience. We recommend that you carry out your own tests in every case to ensure the suitability of our products for the intended process and processing purposes because of the different materials and the working conditions which lie beyond our area of influence. No liability can be derived from this advice or from verbal advice, unless we are responsible for (criminal) intent or gross negligence in this respect.

Revised: 27.12.2021/rk