


DATASHEET

Exterior Waterproofing Corner

Exterior waterproofing corner



- for standard-compliant sealing work
- for secure sealing of external corners

PRODUCT DESCRIPTION

Exterior corner fleece is laminated on both sides and thus the ideal complement to the waterproofing tape in connection with the chemical resistant **Okamul PU-FCA**, liquid **Okamul DF** and the cement based **Servoflex DMS 1K Plus SuperTec** and **Servoflex DMS 1K fast SuperTec** waterproofing products.

PROCESSING

To avoid cracking in corners outside embed the **waterproofing corners** in the first still fresh layer of recommended waterproofing membrane coating it on its surface providing 100% seal. Note the minimum layer thickness of the waterproofing products. Waterproofing tape joints must be overlapped at least 6 cm. Observe technical data sheet for additional information.

PACKAGING

Product description	Item no.	Item no.
10 pieces per box	60181	4015705601816

The aforementioned information, especially the proposals for processing and utilizing our product, is based on our knowledge and experience. We recommend that you carry out your own tests in every case to ensure the suitability of our products for the intended process and processing purposes because of the different materials and the working conditions which lie beyond our area of influence. No liability can be derived from this advice or from verbal advice, unless we are responsible for (criminal) intent or gross negligence in this respect.

Revised: 27.12.2021/rk

Kiesel Bauchemie GmbH u. Co. KG
Wolf-Hirth-Straße 2
D-73730 Esslingen
Phone: 0711 93134-0
Fax: 0711 93134-140
www.kiesel.com
Stuttgart District Court HRA 210806

CEO:
Beatrice Kiesel-Luik
Dirk Schulze

Personally liable partner::
Kiesel Verwaltungsges. mbH
Stuttgart District Court HRB 210484
Registered Office of the company:
73730 Esslingen