

DATASHEET

Interior Waterproofing Corner

Interior waterproofing
corner



- for standt-compliant sealing work
- for secure sealing of internal corners
- for compound sealing with Okamul DF, Servoflex DMS 1K Plus SuperTec, Servoflex DMS 1K-schnell SuperTec and Kiesel sealing membrane
- ideal complement for the Kiesel sealing membrane
- very high alkali resistance

PRODUCT DESCRIPTION

Interior corner fleece is laminated on both sides and thus the ideal complement to the waterproofing tape in connection with the chemical resistant **Okamul PU-FCA**, liquid **Okamul DF** and the cement based **Servoflex DMS 1K Plus SuperTec** and **Servoflex DMS 1K fast SuperTec** waterproofing products.

PROCESSING

To avoid cracking in corners inside embed the waterproofing corners in the first still fresh layer of recommended waterproofing membrane coating it on its surface providing 100% seal. Note the minimum layer thickness of the waterproofing products. Waterproofing tape joints must be overlapped at least 6 cm. Observe technical data sheet for additional information.

PACKAGING

Product description	Item no.	Item no.
10 pieces per box	60180	4015705601809

The aforementioned information, especially the proposals for processing and utilizing our product, is based on our knowledge and experience. We recommend that you carry out your own tests in every case to ensure the suitability of our products for the intended process and processing purposes because of the different materials and the working conditions which lie beyond our area of influence. No liability can be derived from this advice or from verbal advice, unless we are responsible for (criminal) intent or gross negligence in this respect.

Revised: 27.12.2021/rk