

DATASHEET

Okamul WH Plus

Epoxy cleaning agent

- facilitates emulsification and cleaning process
- reduces epoxy film during washing process
- re-emulsifies epoxy film up to 24 hrs
- can be diluted with water
- sprayable



PRODUCT DESCRIPTION

Washing aid for easier emulsifying and cleaning process. Reduces film resin and removes light epoxy film within 24 hours.

SUBSTRATE PREPARATION

As the washing aid in epoxy grouting:

Add **Okamul WH Plus** at maximum 10% to the wash water and start immediately washing with **Okapox royal** or **Okapox royal flooring** grouted coverings using proper scrubbing pad and viscose sponge. Alternatively spray **Okamul WH Plus** on the grouted areas, re-emulsify and clean with clean water. Protect all adjacent surfaces. Make frequent water changes. Rinse again with clean water and clean sponge.

To remove epoxy film:

Use undiluted or in a mixing ratio of max. 1: 1 with water at least 12 hours after grouting. Protect all adjoining surfaces. After a reaction time of max. 15 minutes use white scrubbing pad in circular motion agitating epoxy film. Clean or rinse then with plenty of water.

For cleaning tools such as spatulas, trowels, mixing paddles:

Apply undiluted **Okamul WH Plus** with a brush on existing residues of PU adhesives, **Bakit PU-P**, **Okamul PU-K** epoxy primer and **Okapox GF**. Remove residue with cloth or paper towels first and then rinse it with water.

Check tiles, stone covering and tools for suitability first.

As the adhesive and paint remover:

Apply with a brush undiluted **Okamul WH Plus** in thick layer to remove ink / adhesive layer. Protect all adjacent

areas. After reaction time of 15 minutes remove designated layers with spatula. Clean or rinse then with plenty of water. Try it first in an inconspicuous place for suitability before using it on designated area.

PROCESSING

SPECIFICATIONS

Color	white/ milky
Application	interior/exterior, walls and floors
Density	1,004 kg/dm ³
Application temperature	+10 °C to +30 °C (50 °F to 86 °F)
Flashpoint	> 91 °C
GISCODE	S 1 according to TRGS 610
Storage	24 month in a cool place

IMPORTANT NOTICE

Avoid direct skin contact and use proper rubber gloves and goggle protection. Ensure good ventilation. Avoid contact with plastics or natural stones (limestone).

COVERAGE

As epoxy film remover: ca. 50-100 g/m²
 Wash additive: ca. 30-60 g/m²

TOOLS

Brush, white scrubbing pad, viscose sponge

CLEANING

Clean tools immediately with water.

PACKAGING

Product description	Item no.	Item no.
4 x 1 liter-plastic-bottles	50009	4015705500096
5 liter-plastic-canister	50008	4015705500089
25 liter-plastic-canister	50010	4015705500102

The aforementioned information, especially the proposals for processing and utilizing our product, is based on our knowledge and experience. We recommend that you carry out your own tests in every case to ensure the suitability of our products for the intended process and processing purposes because of the different materials and the working conditions which lie beyond our area of influence. No liability can be derived from this advice or from verbal advice, unless we are responsible for (criminal) intent or gross negligence in this respect.

Revised: 23.04.2019/me