

## DECLARATION OF PERFORMANCE

No. 11275G

In accordance with Appendix III of the Regulation (EU) No. 305/2011 for the product

### **Servoflex-Trio-SuperTec (grey)**

1. Unambiguous identification code for the product type:

**EN 12004 C2E-S1**

2. Type, batch or serial number or another identification marking  
for the building product in accordance with article 11 paragraph 4:

**Batch number: See product packaging**

3. Purpose intended by the manufacturer or intended  
purposes of the building product in accordance with the applicable harmonised  
technical specification:

**Flexible cement-containing tile adhesive for more stringent requirements with  
extended open time**

4. Name, registered trade name or registered brand and contact address of the  
manufacturer in accordance with article 11 paragraph 5:

**Kiesel Bauchemie GmbH u. Co. KG  
Wolf-Hirth-Str. 2  
73730 Esslingen**

5. Name and contact address of the representative commissioned with the tasks in accordance  
with article 12 paragraph 2:

**Not relevant**

6. System or systems for assessment and inspection of the constancy of performance of the  
building product in accordance with Appendix V:

**System 3**

7. In case of a declaration of performance which concerns a building product which is included in a  
harmonised standard:

The notified body, MPA Stuttgart, code number 0672, has conducted the type test on the product with regard to the classification in accordance with EN 12004:2007, and has issued the following:  
**Test Report 12-9.011.962 / P1 / Mil**

8. In case of a declaration of performance which concerns a building product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

| Important characteristics                               | Performance               | Harmonised technical specification |
|---------------------------------------------------------|---------------------------|------------------------------------|
| Fire behaviour                                          | Class E <sub>fl</sub>     | 12004:2007+A1:2012                 |
| Adhesive tensile strength after dry storage             | $\geq 1.0 \text{ N/mm}^2$ |                                    |
| Adhesive tensile strength after water immersion         | $\geq 1.0 \text{ N/mm}^2$ |                                    |
| Adhesive tensile strength after warm storage            | $\geq 1.0 \text{ N/mm}^2$ |                                    |
| Adhesive tensile strength after frost/thaw test storage | $\geq 1.0 \text{ N/mm}^2$ |                                    |

10. The performance of the product in accordance with numbers 1 and 2 accords with the declared performance in accordance with number 9. The manufacturer holds sole responsibility for the preparation of this declaration of performance in accordance with number 4.

The manufacturer *Kiesel Bauchemie GmbH u. Co. KG*

Dr. Matthias Hirsch

-Technical Managing Director-

Esslingen, July 2013